



Modell: H-428

Art.: 88885665

7in1 USB Type C hub

With its many interfaces, the H-428 offers a wide range of connection options for HDMI, RJ45 or USB devices.

Memory cards in MicroSD(TF) and SD/MMC formats can also be easily read with the H-428.

The package is rounded off by a USB Type C PD charging socket so that you can continue to charge your cell phone or supply your notebook with power while using the H-428.

Output	Connection	USB Type C
	Transfer rate	USB 3.2 Gen1/ 5GBps

Input	USB C	PD version: PD 3.0
		PD voltage: 5V - 20V=
		PD current: Max 3A

	USB A	2x USB 3.2 Gen1/ 5 GBps
--	-------	-------------------------

	Video Interface	HDMI 2.0 (Audio) Resolution: 4096x2160@30Hz, 3840x2160@30Hz
--	-----------------	--

	Ethernet	RJ-45 (Gigabit Ethernet) Transfer rate: 1000 Mbps (Half Duplex) / 1000 Mbps (Full Duplex) IEEE 802.3az, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x - Supports Wake on LAN Funktion, Suspend Mode, Remote WakeUp via Link-Change, Magic Packet/ Microsoft WakeUp. - Supports IEEE 802.1Q VLAN Tagging, IEEE 802.P Layer 2 priority encoding - Supports Jumbo Frame to 9K bytes - Supports Checksum Offload (IPv4, IPv6, TCP, UDP), TCP Large Send Offload
--	----------	--

	Card Reader	1x Micro SD (TF) 1x SD/MMC
--	-------------	-----------------------------------

Environmental	Temperature	-20°C - 40°C (operating) -20°C - 55°C (storage)2
	Humidity	0-80% (operating, non condensing) 20-90% (storage, non condensing)

Scope of delivery	7in1 Card Reader Manual
--------------------------	----------------------------

Warranty	24 Months
-----------------	-----------

Logistic data

Net weight	0,070 kgs
Gross weight	0,095 kgs
Article number	88885665
GTIN	4260455649315
Packing unit	1 pcs
	40 pcs (carton)