# X-608 Infinity Micro









### X-608 Infinity Micro - small level Infinity-Mirror

Inter-Tech Elektronik Handels GmbH

An infinity mirror in the front illuminated by RGB LEDs, an RGB LED strip in the power supply tunnel and the standard 120mm RGB fan make the X-608 a real eye-catcher. The front made of tempered glass and the side panel made of 4mm thick tempered glass, which opens like a door, give a generous view of strong effects and colors, which are provided by switches on the front or via the 5V RGB header connector (addressable RGB LEDs). Plenty of room for additional fans or water cooling can be found in the spacious interior of the X-608.

On the top of the case are a removable dust filter and the controls. In addition to the HD audio sockets, there is a USB 3.0 Type A and USB 3.0 Type C connection as well as two separate switches for controlling the brightness and the effects. A dust filter in the power supply tunnel and silent blocks, on which the power supply is stored, allow a quiet and clean operation. The X-608 leaves nothing to be desired with a removable hard disk mounting frame, a holder for long graphics cards, the included RGB sync cable and a wide range of cable laying options.

- ✓ Front panel made of tempered glass with RGB Infinity-Mirror
- ✓ Window side panel made of 4mm thick tempered glass with door hinge
- √ 120mm RGB fan and RGB LED-strip included
- √ 3pin RGB header connector for 5V RGB motherboard control

# X-608 Infinity Micro

### **Specifications**

Inter-Tech Elektronik Handels GmbH

Motherboard

Max. Drive Bays

5.25" external: 0
3.5" external: 0
3.5" internal: 2\*
2.5" internal: 5\*

Front Connectors

USB 3.0: 1

USB 3.0 Type C: 1

Microphone: 1 Speaker: 1

Cooling System Front: 3x 120mm

(optional)

Rear: 1x 120mm (serial, RGB, 3pin-connector)

Top: 2x 120mm

(optional)

Max CPU-Cooler height150mmMax Graphic card length320mmPacking UnitsShipping unit: 1 pcsWarranty24 Months

Article Number 88881315
EAN-Code 4260455644730
Scope of Delivery Screw set

RGB sync cable

Graphics cards bracket

Manual

(German)

Features Front panel with Infinity-Mirror-Effect made of tempered glass

Window side panel made of 4mm thick tempered glass

Window side part swiveling for easy disassembly

Integrated RGB LED-Strip on the PSU tunnel

1x 120mm serial RGB fan at the rear installed Switch for manual brightness adjustment of the RGB LEDs

RGB-/PWM-board for up to 5 RGB-devices

(in combination with mainboard with PWM function up to 5 fans with 3pin-connector)

3pin RGB header connector for 5V RGB motherboard control

Two 3.5" mounting options underneath the mainboard tray with separated airflow

Option to mount liquid coolers in 120mm and 240mm

Easy removable dust filters in the cap and the bottom Decoupled PSU mounting in separated tunnel at the bottom

Reusable slot brackets

Cable management

USB Type C internally as USB 3.0 connector

Stands

\*can vary due to combinations



## X-608 Infinity Micro

### **Dimensions and Weight** Cage Case Package Height 390mm 415mm 475mm Width 195mm 195mm 270mm 470mm Depth 350mm 405mm Weight (net): 5.84kg Weight (gross): 6.84kg

ower Supply	L	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4
P8 12V 8Pin	_ · _	
PCI-Express 6+2Pin	460	ur
PCI-Express in	tho	
IDE 4Pin		-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

