





IP-60

The IP-60 is a case for Mini-ITX mainboards with external power supply and I/O shields in normal height.

Thanks to the closed design and the integrated cooling fins, it is the ideal candidate for a system with passive cooling. In conjunction with the optional IP-3 cooler, CPUs with a TDP of up to 70W can be installed and operated entirely without active fan elements. Alternatively, other CPU coolers up to 43mm in height can also be installed.

The case can be attached to almost any supporting surface (e.g. on the wall) using the standard mounting brackets, optionally using the additionally available VESA mount behind the monitor or as a standing device with four feet. Data can also be conveniently uploaded via the two integrated USB 3.0 front connections.

- Compact Mini-ITX housing made of aluminum
- ✓ Integrated cooling fins for heat dissipation
- ✓ Wall mounting via standard rails
- ✓ Two USB 3.0 front ports



F



Specifications	
Motherboard	Mini ITX Maximum board dimensions WxD: 170mm x 170mm , 6.7" x 6.7"
Max. drive bays	5,25" external: 0 3,5" external: 0 3,5" internal: 0 2,5" internal: 2
Front connectors	USB 3.0: 2
Cooling system	-
Control elements	Power button
LED	Power
	HDD activity
Power supply	Mini-ITX PSU
Material	Aluminum
Max. CPU cooler height	43mm
Packing units (VE/VPE/PAL)	1/6/120
Warranty	24 Months
Article number EAN-Code	88887372 4260455647618
Scope of delivery	Screw Set
Scope of derivery	Wall mount
	Four feet
	Manual
	(englisch)
	Mounting bracket for IP-3
	Mini-ITX-PSU 120W
Features	Possibility on the back for 1x serial port
	Possibility on the back for 1x WLAN
	Possibility for optional USB 3.2 Type C socket VESA mount optional (Art. 88885468)

Dimensions and Weight						
		Cage	Case	Package		
	Height	58mm	77mm	250mm		
	Width	195mm	210mm	160mm		
	Depth	236mm	240mm	315mm		
Weight (net): 1.68kg Weight (gross): 2.05kg						

CE

Certification:

