IPC 1U-10248

IPC 1U-10248

The **IPC 1U-10248** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 1U-10248** provides the possibility to mount eight 2.5" internal hard drives. Two standard 40mm fans guarantee an optimal cooling.

Additional extras like easily reachable USB 3.0 connectors and the universal ATX I/O plate complete this total package.

Errors excepted. No warranty for the correctness of the information State: 30.07.2020

IPC 1U-10248

Specifications

Motherboard	Mini ITX, mATX, µATX, ATX, SSI CEB maximal motherboard size WxD: 305mm x 270mm, 12" x 10.6"
Drive Bays	5.25" external: 2* 3.5" internal: 2* 2.5" internal: 8*
Front Connectors	USB 3.0: 2
Cooling System	Internal: 2x 40mm (included, 3pin (4pin connector))
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity Alert
Power Supply	1U, 1U redundant, FLEX-ATX with Adapter 88885341
Material	1.0-1.2mm Steel
Maximum CPU cooler height	32mm
Maximum graphics card length	270mm
Packing Units	Shipping Unit: 1 Piece Pallet: 30 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887100
EAN-Code	4260133126213
Scope of Delivery	Screw Set Mounting bracket for FLEX-ATX PSU
Features	2x 40mm fan included USB 3.0 as block connector Universal ATX I/O plate 1x Riser slot

*can vary by using several mounting options

Dimensions and Weight

	Cage	Case	Package
Height	44.5mm	44.5mm	110mm
Width	433mm	482mm	545mm
Depth	480mm	508mm	660mm

Weight (net): 5.60kg
Weight (gross): 7.44kg

Power supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	-

Without

Certification: CE

Errors excepted. No warranty for the correctness of the information State: 30.07.2020