



IPC 2U-2408

The **IPC 2U-2408** is the ideal case for a small and cheap server solution. With its excellent quality and finish, Inter-Tech established the basis for a very variable case.

The **IPC 2U-2408** offers the possibility to mount maximal eight 2.5" or 3.5" Hot-Swap HDDs, one Slim DVD, two internal 3.5" and three internal 2.5" HDDs. The **IPC 2U-2408** has four 80mm fans, which are mounted directly at the back of the drive brackets and ensure a reliable and optimal cooling.

Additional extras like the reusable and perforated slot brackets and the lid with the snap locks round off the picture.

Specifications

Motherboard	Mini ITX, µATX, ATX, eATX, SSI EEB maximal motherboard size WxD: 305mm x 345mm, 12" x 13.5"
Drive Bays	8x 2.5" or 3.5" Hot-Swap (max. 12G) 1x drive bay Slim DVD for 1x Slim DVD or 1x 2.5" internal hard drive 2x drive bays 3.5" for 1x 3.5" or 1x 2.5" internal hard drive
Front Connectors	USB 3.0: 2
Cooling System	Internal: 4x 80mm (included, Molex connector)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity
Power Supply	2HU Server Power Supply
Material	1.0-1.2mm Steel
Maximum CPU cooler height	65mm
Maximum graphics card length	345mm
Packing Units	Shipping Unit: 1 piece Pallet: 21 pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887117
EAN-Code	4260133126381
Scope of Delivery	Screw Set Assembly tool Mounting brackets for 2HU PSU
Features	4x 80mm fan included Reusable Los Profile slot brackets USB 3.0 as block connector Snap locks Hot-Swap backplane with SFF-8087 socket (max. 12G) ¹

¹ The backplane is only compatible with a SAS-Controller with SFF-8087 connector.
To use the backplane with a SATA controller please order the optional SFF 8087 cross over cables (Art no.: 88885237) in right quantity.

Dimensions and Weight

	Cage	Case	Package
Height	89mm	89mm	155mm
Width	433mm	481mm	560mm
Depth	650mm	688mm	830mm

Weight (net): 10.10kg
Weight (gross): 12.36kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification:

