



19" IPC 2098-SL 2U -

Classic 19" Rack with a lot of space for different drives

You can remove the HDD cages with a few steps for easy mounting of internal devices.

On top you can mount an ATX PSU with 80mm fan to get a cost-efficient and professional solution.

Alternatively you can mount a 2U PSU.

The lockable doors in front of the slots prevent unauthorized access.

Integrated air filters ensure clean air and a flawless cooling.

Specifications

Motherboard	Mini ITX, mATX, µATX, ATX
Max. Drive Bays	maximal motherboard size WxD: 305mm x 290mm, 12" x 11.4"
	5.25" external: 1
	3.5" external: 1*
	3.5" internal: 5*
	2.5" internal: 3*
Front Connectors	USB 3.0: 2
Cooling System	Front: 2x 60mm (optional) Inside: 4x 80mm (3x included, Molex connector, 1x optional)
Controls	Power-Button Reset-Button
LED	Power HDD Activity
Power Supply	ATX PSU with 80mm fan, 2U PSU
Material	1.0-1.2mm Steel
Maximum CPU cooler height	65mm
Maximum graphics card length	290mm
Packing Units	Shipping Unit: 1 Piece Pallet: 20 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887127
EAN-Code	4260133128071
Scope of Delivery	Keys, Screw Set
Features	Air filter Removable HDD cages 4x screwed Low Profile brackets (backside) Lockable front doors 2x USB 3.0 internal as block connector

*can vary by using several mounting options

Dimensions and Weight

	Cage	Case	Package
Height	87mm	89mm	175mm
Width	427mm	485mm	545mm
Depth	565mm	615mm	720mm

Weight (net): 8.72kg
Weight (gross): 10.80kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification:

