

## IPC 3098-S



### 19" IPC 3098-S 3U - Classic 19" Rack with a lot of space for different drives

You can remove the HDD cages with a few steps for easy mounting of internal devices.

5 mounting slots with full height and the possibility to mount an ATX PSU ensures a professional and cost efficient solution.

The lockable doors in front of the slots prevent, unauthorized access.

Integrated air filters ensure clean air and a flawless cooling.



# IPC 3098-S

#### **Specifications**

Motherboard	Mini ITX, mATX, μATX, ATX
	maximal motherboard size WxD: 305mm x 300mm, 12" x 11,8"
Max. Drive Bays	5.25" external: 4
	3.5" external: 0
	3.5" internal: 5*
	2.5" internal: 6*
Front Connectors	USB 3.0: 2
Cooling System	Rear: 2x 60mm
	(included, Molex connector)
Controls	Power-Button
	Reset-Button
LED	Power
	HDD Activity
Power Supply	ATX PSU
Material	1.0-1.2mm Steel
Maximum CPU cooler height	113mm
Maximum graphics card length	300mm
Packing Units	Shipping Unit: 1 Piece
	Pallet: 23 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887176
EAN-Code	4260133128088
Scope of Delivery	Key
	Screw Set
Features	Air filter
	Removable HDD cages
	4x screwed brackets
	(backside) Lockable front doors
	*can vary by using several mounting options
	22 2, 2, 22g 23.000 moduling opcorb

### **Dimensions and Weight**

	Cage	Case	Package
Height	137mm	133mm	225mm
Width	427mm	485mm	560mm
Depth	470mm	530mm	630mm
eight (net): eight (gros:	: 9.34kg s): 11.12kg	9	

ower Supply	<i>'</i>	
<u> </u>	_	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4.
P8 12V 8Pin	-	_ 4 🗗
PCI-Express 6+2Pin	tho	
PCI-Express Clin		
IDE 4Pin	tnv	-
S-ATA		-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification: