



IPC 3U-3508

The **IPC 3U-3508** is the perfect rack for a small and cost-effective storage system. Due to the excellent material quality, in combination with excellent workmanship, Inter-Tech has created the basis for an extremely variable case.

The case offers the possibility to install eight 2.5" or 3.5" Hot-Swap HDDs and two 5.25" external drives or two internal 2.5" HDDs.

The **3U-3508** has two 80mm fans included and space for two more optional 60mm fans to ensure reliable and optimal cooling.

Two USB 3.0 connectors in the front complete the offer

Specifications

Mainboard	Mini ITX, µATX, ATX
Drive bays	Max. Mainboard size BxT: 305mm x 244mm, 12" x 9.6" 2.5" or 3.5" external Hot-Swap (max. 6G): 8 5.25" external: 2 2.5" internal: 2
Front connectors	USB 3.0: 2
Cooling system	Internal: 2x 80mm (Molex) Rear: 2x 60mm (optional)
Controls	Power button Reset button
LED	Power HDD activity
Power supply	ATX PSU Redundant PSU
Material	1.0-1.2mm Steel
Maximum CPU cooler height	100mm
Maximum graphics card length	244mm
Packing units	Shipping unit: 1 piece Pallet: 15 pieces
Warranty	24 months
Article number	88887335
EAN-Code	4260455646420
Scope of delivery	Screws Mounting bracket for ATX power supplies
Features	Serial 2x 80mm fans 5x perforated slot brackets 2x 4-way S-ATA/SAS hot-swap backplane with SATA socket Lockable Hot-Swap frame

Dimensions and Weight

	Cage	Case	Package
Height	132mm	132mm	245mm
Width	430mm	482mm	575mm
Depth	478mm	528mm	655mm

Weight (net): 9.51kg
Weight (gross): 12.47kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification:

