



IPC 5U-5512

The **5U-5512** is the ideal case for a small and cheap server solution. With its excellent quality and finish, Inter-Tech established the base for a very variable case.

It offers the possibility to install twelve 2.5" or 3.5" Hot-Swap HDDs lockable tray, two 5.25" external devices, five 2,5" HDDs and motherboards up to E-ATX size.

The **5U-5512** has three 80mm fans included and space for two more optional 80mm fans to ensure reliable and optimal cooling.

Additional extras like reusable and perforated slot brackets and two USB 3.0 connectors complete the offer.

Specifications

Mainboard	Mini ITX, µATX, ATX, eATX, SSI EEB*
Drive Bays	Max. Mainboard size WxD: 305mm x 345mm, 12" x 13,5" 2,5" or 3,5" external Hot-Swap (max. 6G): 12 5,25" external: 2 2,5" internal: 1 Middle tray 2,5": 4
Front Connectors	USB 3.0: 2
Cooling System	Internal: 3x 80mm (included, Molex connector) Rear: 2x 80mm (optional)
Controls	Power-Button Reset-Button
LED	Power HDD Activity
Power Supply	ATX / Redundant PSU
Material	1.0/1.2mm Steel
Maximum CPU cooler height	105mm
Maximum graphics card length	250mm
Packing Units	Shipping Unit: 1 piece Pallet: 9 pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887337
EAN-Code	4260455646444
Scope of Delivery	Screw set Mounting bracket for ATX (preassembled), 4U redundant PSU
Features	3x 80mm fans included Drive brackets removable USB 3.0 as block connector 7x perforated slot bracket (rear) S-ATA/SAS Hot-Swap Backplanes mit SATA Buchsen Lockable Hot-Swap tray

Dimensions and Weight

	Cage	Case	Package
Height	225mm	225mm	330mm
Width	430mm	481mm	575mm
Depth	475mm	505mm	655mm

Weight (net): 13.56kg
Weight (gross): 16.87kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification:

