



IPC 6U-6606

The **IPC 6U-6606** is the ideal case for a small and cheap server solution. With its excellent quality and finish, Inter-Tech established the base for a very variable case.

It offers the possibility to install six 2.5" or 3.5" Hot-Swap HDDs with lockable tray, one 5.25" external device, seven 2,5" and nine 3.5" internal HDDs.

The **6U-6606** has a lockable front, removable dust filters and three 120mm fans included. Space for two more optional 80mm fans ensure reliable and optimal cooling.

Additional extras like the reusable and perforated slot brackets, the USB 3.0 connectors and the lid with the snap lock complete the offer.

Specifications

Mainboard	Mini ITX, µATX, ATX, eATX
Drive Bays	Max. Mainboard size WxD: 305mm x 330mm, 12" x 13" 2,5" oder 3,5" extern Hot-Swap (max. 6G): 8 5,25" extern: 1 3,5" intern: 9 2,5" intern: 3 Middle tray 2,5": 4
Front Connectors	USB 3.0: 2
Cooling System	Internal: 3x 120mm (included, Molex connector) Rear: 2x 80mm (optional)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 2x Network Activity
Power Supply	ATX-/ PS/2 Redundant PSU
Material	1.0/1.2mm Steel
Maximum CPU cooler height	135mm
Maximum graphics card length	330mm
Packing Units	Shipping Unit: 1 piece Pallet: 9 pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887339
EAN-Code	4260455646468
Scope of Delivery	Screw set Mounting bracket for ATX (preassembled)
Features	3x 120mm fan included USB 3.0 as block connector 7x perforated slot bracket (rear) S-ATA Hot-Swap backplane with SATA socket Lockable Hot-Swap tray

Dimensions and Weight

	Cage	Case	Package
Height	285mm	285mm	375mm
Width	428mm	482mm	575mm
Depth	550mm	600mm	705mm

Weight (net): 20.14kg
Weight (gross): 23.96kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification:

