



## IPC 1.5U-1528-1

The **1.5U-1528-1** is the perfect rack for a small server system. The special design in 1.5U enables you to run an external drive (2.5" or 3.5") in Hot-Swap mode on an ITX-Mainboard base. The interior offers the option to mount two additional 2.5" drives and more height for CPU-cooler than a regular 1U case.

Two serial 60mm fans behind the front panel ensure a reliable cooling. It also offers two USB front connectors in the front, next to the controls.

- ✓ more space than 1U racks
- ✓ 2x 60mm Fan
- ✓ Depth only 280mm
- ✓ Aluminum front

## Specifications

Motherboard	Mini-ITX
Max board dimensions WxH: 170mm x 170mm, 6.7" x 6.7"	
Drive Bays	2.5" or 3.5" Hot-Swap (max. 6G): 1 2.5" internal: 2
Front Connectors	USB 2.0: 2
Cooling System	Front: 2x 60mm (serial, Molex connector)
Controls	Power-Button Reset-Button
LED	Power HDD Activity
Material	1.0-1.2mm Steel Front Aluminum
Maximum CPU cooler height	40mm
Maximum graphics card length	245mm
Packing Units	Shipping unit: 1 Piece Pallet: 32 Pieces
Warranty	24 Months
Article Number	88887377
EAN-Code	4260455647892
Scope of Delivery	Screw Set
Features	Option to mount Flex-ATX PSU's Only 280mm Depth (without grips) 2x 60mm serial fans Two Riser-Slots for expansion cards (full height max. 7cm depth, half height max. 9cm depth) USB 2.0 internal block connector

## Dimensions and Weight

	Cage	Case	Package
Height	65mm	65mm	185mm
Width	423mm	482mm	430mm
Depth	280mm	314mm	560mm

Weight (net): 4,11kg  
Weight (gross): 5,56kg

## Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

**Certification:**



