



## Model: SA-0816

Art.: 88887393

The PDU SA-0816 is a switchable power strip, intended for installation in 19" server cabinets, which can be operated via web interface or SNMP.

All 8 outputs can be switched individually via remote access.

The individual current consumption and individual voltage can be queried via the web interface.

A cascade input and output allows to connect several PDUs of SA-series and control them together via one access.

Using the included sensor, temperature and humidity can be monitored via the web interface.

<b>Features</b>		Remote Monitoring by Webinterface or SNMP
		Measure of current, voltage and power
		Adjustable warning values
		HTTP/HTTPS, DHCP, SNMP
		E-Mail notification
		User management
		Measure of temperatur and humidity using the included sensor
<b>Input</b>	Input voltage	AC 100 - 240 V~, 50/60 Hz
	Current	max 3600W
	Connector	1x C20
<b>Output</b>	Output voltage	AC 100 - 240 V~, 50/60Hz
	Max. output	16A
	Max. output/ port	10A
	Connectors	8x C13
<b>Remote-control</b>	Network	1x RJ45, 10/100M
	Cascade input/output	2x RJ45, 10/100M
	Temperature sensor	1x RJ11
	Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, SNMP, Mail
<b>Safety</b>	Over power protection	+
<b>Environmental</b>	Temperature	0°C - 50°C (Operation) -20°C - 60°C (Storage)
	Humidity	0% - 80% (Operation, non condensing) 0% - 85% (Storage, non condensing)
<b>Scope of delivery</b>		PDU Power cord C19 to C20 Temperature sensor Short instructions, English + German

### Warranty

24 Months

### Logistic data

Dimension 442 x 172 x 44 mm

Net weight 2.165 kgs

Gross weight 2.680 kgs

Article number 88887393

GTIN 4260455648882

Packing unit 1 pcs/ 4 pcs