



Model: SX-0816

Art.: 88887426

19"-PDU with 8 switchable C13 outlets for professional remote power distribution and monitoring in server and network cabinets. The maximum total load is 16 A, with each individual outlet capable of handling up to 10 A. Each port can be switched individually via remote access, enabling targeted control and a reboot function for connected devices.

The integrated monitoring system reliably records total current, total voltage, and total power, ensuring transparent energy monitoring. Additionally, a temperature and humidity sensor is integrated to ensure optimal environmental conditions in the rack and to enable an early response to critical changes.

Management is conveniently handled via a web interface or SNMP and supports a wide range of network protocols, including HTTP, HTTPS, DHCP, SNMP, TCP/IP, UDP, and email notifications. Customizable warning and alarm thresholds enable proactive monitoring and automatic notifications when thresholds are exceeded.

The PDU features one C20 input and eight C13 outputs and is ideal for data centers, server racks, network environments, and professional IT infrastructures where reliable power distribution, remote control, and environmental monitoring are required.

| | | |
|--------------------------|-----------------------|---|
| Features | | <p>Remote monitoring via web interface or SNMP</p> <p>Measurement of current, voltage, and power (total measurement)</p> <p>Configurable alert thresholds</p> <p>HTTP/HTTPS, DHCP, SNMP</p> <p>Email notifications</p> <p>User management</p> <p>Temperature and humidity measurement via built-in sensor</p> |
| Input | Input voltage | AC 100 - 240 V~, 50/60 Hz |
| | Current | max 3840W |
| | Connector | 1x C20 |
| | Length power cord | 2 m |
| Output | Output voltage | AC 100 - 240 V~, 50/60Hz |
| | Max. output | 16A |
| | Max. output/ port | 10A |
| | Connectors | 8x C13 |
| Remote-Control | Network | 1x RJ45, 10/100M |
| | Protokolc | TCP/IP, UDP, HTTP, HTTPS, DHCP, SNMP, Mail |
| Safety | Over power protection | + |
| Environmental | Temperature | 0°C - 50°C (Operation) -20°C - 60°C (Storage) |
| | Humidity | 0% - 80% (Operation, non condensing) 0% - 85% (Storage, non condensing) |
| Scope of delivery | | <p>PDU</p> <p>Mounting brackets and screws</p> <p>C19 to C20 connection cable</p> <p>Short instructions, English + German</p> |
| Warranty | | 24 Months |

Logistic data

| | |
|----------------|-------------------|
| Dimension | 442 x 170 x 44 mm |
| Net weight | 2.30 kg |
| Gross weight | 2.88 kg |
| Article number | 88887426 |
| GTIN | 4262531060007 |
| Packing unit | 1 pcs/ 4 pcs |