



The **KVM AS-91xx DLS** series consists of a professional KVM console with extendable keyboard unit and 19" TFT LED monitor. The console is mainly used in server cabinets in which one or more servers are installed, which can be operated centrally via the **KVM AS-91xx DLS** thanks to the integrated switching option.

The integrated password protection also prevents access to keyboard and monitor and additionally protects your servers from unauthorised operation.

The console is connected to the servers via the supplied system cables DVI/USB to DVI/USB.

- ✓ Energy saving LED-Monitor
- ✓ Password protection
- ✓ 1080p Resolution
- ✓ 24 months warranty

## Specification

|                           |                                                                                                                                                                                                                                                                                             |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Keyboard                  | QWERTY-Keyboard/ Keypad                                                                                                                                                                                                                                                                     |
| Monitor                   | 19" TFT LED                                                                                                                                                                                                                                                                                 |
| Max. connectable PCs      | 256                                                                                                                                                                                                                                                                                         |
| Suitable for racks        | 800-1000mm                                                                                                                                                                                                                                                                                  |
| Minimal mounting depth    | 385mm                                                                                                                                                                                                                                                                                       |
| Maximal mounting depth    | 690mm                                                                                                                                                                                                                                                                                       |
| Connectors                | modular<br>Power                                                                                                                                                                                                                                                                            |
| Keys                      | 12x KVM, 1x Power, 5x TFT-Menue                                                                                                                                                                                                                                                             |
| Supported OS              | No limitation                                                                                                                                                                                                                                                                               |
| Switch Mode               | Hotkey<br>OSD Menue                                                                                                                                                                                                                                                                         |
| Switch scan time          | 1-255s<br>(OSD adjustable)                                                                                                                                                                                                                                                                  |
| DDC                       | •                                                                                                                                                                                                                                                                                           |
| Display resolution        | Nativ: 1366x768, 75Hz<br>(max. 1920x1080, 60 Hz interpolated)                                                                                                                                                                                                                               |
| Display frequency         | 75Hz                                                                                                                                                                                                                                                                                        |
| Display brightness        | 300lm                                                                                                                                                                                                                                                                                       |
| Display contrast          | 1000:1                                                                                                                                                                                                                                                                                      |
| Power supply              | External adapter                                                                                                                                                                                                                                                                            |
| Input                     | 12V, 5A                                                                                                                                                                                                                                                                                     |
| Material                  | Noncorroding steel                                                                                                                                                                                                                                                                          |
| Operation temperature     | -10°C~60°C                                                                                                                                                                                                                                                                                  |
| Storage temperature       | -30°C~70°C                                                                                                                                                                                                                                                                                  |
| Humidity                  | 0-80%                                                                                                                                                                                                                                                                                       |
| MTBF                      | average 120000 hrs                                                                                                                                                                                                                                                                          |
| Package dimension (h/w/d) | 190x610x715mm                                                                                                                                                                                                                                                                               |
| Packing unit              | Parcel: 1 pcs<br>Pallet: 15 pcs                                                                                                                                                                                                                                                             |
| Warranty                  | 24 months                                                                                                                                                                                                                                                                                   |
| Scope of delivery         | 19" mounting kit<br>System cable USB/DVI/Audio auf USB/DVI/Audio (180cm)<br>(quantity depending model)<br>15cm VGA cable for IKVM connection<br>External power adapter<br>(Input: 110V-240V 60W Output: 12V 5A)<br>Power cord<br>Quick start manual<br>(German)<br>Manual on CD<br>(German) |
| Features                  | 12x Hotkeys<br>Password protection for keyboard and mouse<br>Front USB-Port for additional keyboard or mouse                                                                                                                                                                                |

• = Yes  
- = No

| Article number | EAN           | Name        | Port qty | Net. weight | Gros weight | Dimension (hxxwxd) |
|----------------|---------------|-------------|----------|-------------|-------------|--------------------|
| 99997209       | 4260455645850 | AS-9100 DLS | 1        | 10.175 kg   | 14.615kg    | 44.5x482x530mm     |
| 99997210       | 4260455645867 | AS-9104 DLS | 4        | 13.76 kg    | 18.56kg     | 44.5x482x615mm     |
| 99997211       | 4260455645874 | AS-9108 DLS | 8        | 15.335kg    | 19.135kg    | 44.5x482x615mm     |