



Model: PD-3100

Art.: 88882230

PD charger PD-3100 for international use.

The PD-3100 is a normal PD charger with an output power of 100W and output voltages of 5V, 9V, 12V, 15V and 20V. The special feature of the PD-3100 is the interchangeability of the input plugs. This means that the PD-3100 can be operated throughout Europe, Great Britain, the USA and in areas compatible with these countries. This makes it an ideal companion on your next vacation trip.

Input	Voltage	AC 100 - 240 V ~
	Current	max 2A
	Frequency	50/60Hz
Output	Power	max. 100W
	Current	max. 5.0A
	Voltage	5V= (max. 3.0A) 9V= (max. 3.0A) 12V= (max. 3.0A) 15V= (max. 3.0A) 20V= (max. 5.0A)
	Adapter	Europe UK USA
	Protocols	PD 2.0/ 3.0
	Connector	USB Type C
	Cable length	2 m
Safety	Short circuit protection	+
	Over power protection	+
	Over voltage protection	+
Economic data	Efficiency	up to 90.81%
	Standby consumption	< 0.09W
	MTBF	> 50,000 hrs
Environmental	Temperature	0°C - 40°C (Operating) -20°C - 70°C (Storage)
	Humidity	20% - 80% (Operating, non condensing) 10% - 90% (Storage, non condensing)
Scope of delivery		Power supply One adapter each for EU, GB, USA USB Type C cable, 2 m Manual
Warranty		24 months

Logistic data

Dimension	66 x 67 x 32 mm
Net weight	285 g
Gross weight	395 g
Article number	88882230
GTIN	4260455648912
Packing unit	1 pcs