



Model: TFX-300-X BULK

Art.: 88882260

The **TFX 300-watt power supply** was developed specifically for compact PC systems and offers high performance and outstanding reliability despite its small size. It is ideal for small form factor PCs (SFF), HTPCs, industrial and office systems, or as a replacement power supply for OEM cases. The modern component selection and integrated protection circuits ensure safe and efficient continuous operation.

Features:

- **Compact TFX format:** Perfect for flat and space-saving cases.
- **300 watts output power:** Sufficient for office PCs, media systems, and light graphics solutions.
- **High stability & efficiency:** Clean power supply for all system components.
- **Quiet, temperature-controlled fan:** Ensures quiet operation and effective cooling.
- **Extensive protection functions:** OVP, OCP, SCP, and OPP for maximum safety.

Features		300 Watt TFX power supply PCIe connector 6+2pin
Input	Input voltage	AC 230 V~
	Frequency	50 Hz
	Current	4A @230V
Output	Output voltage	Current
	+ 3.3V	max. 10A
	+ 5V	max. 12A
	+ 12V	max. 20A
	- 12V	max. 0.5A
	+ 5Vsb	max. 2.0A
	Total power	max. 300W
	Power 3.3V + 5V	max. 80W
Safety	<u>Over voltage protection</u>	+
	<u>Under voltage protection</u>	+
	<u>Short circuit protection</u>	+
	<u>Over current protection</u>	+
Environmental	Temperature	0°C - 40°C (operating) -35°C - 70°C (storage)
	Humidity	10% - 90% (operatig, non condensing) 50% - 95% (storage, non condensing)
Scope of delivery		Power supply Power cord
Warranty		24 Months

Logistic data

Dimension	175 x 85 x 65 mm
Net weight	0.91 kg
Gross weight	0.93 kg
Article number	88882260
GTIN	4260455649704
Packing unit	1 pcs 10 pcs (parcel)

Cable configuration

