



## SMA-6406

The SMA-6406 wall-mounted rack stands out for its low height of just 6U and a depth of only 450mm, offering a space-saving alternative compared to large and bulky server & network cabinets.

With a material thickness between 1.25 and 1.50 mm, the wall-mounted rack carries a total load of up to 30kg and also complies with the IP20 protection class. The rack is powder-coated in the colour RAL 9005 and can be closed both by the integrated door made of tempered glass and by the individually removable side panels. Cable inlets in the lid and in the floor also ensure a clean routing of the cables. Two optional 120mm fans, which find their place in the lid, support the case during ventilation.

- ✓ 6U and 450mm depth
- ✓ Total loading capacity of up to 30kg
- ✓ Meets protection class IP20
- ✓ Lockable glass door and side panels

## Specifications

Unit	6U
Width	600mm
Depth	450mm
Max. loading capacity	30kg
Material front door	Tempered Glass
Opening angle of the door	180°
Colour	RAL 9005
IP class	Fulfills IP20
Dimensions (H/W/D)	368x600x450mm
Package dimensions (H/W/D)	250x485x630mm
Weight (net)	14.44kg
Weight (gross)	16.22kg
Packing units (VE/VPE)	1/14
Garantie und Gewährleistung	24 Months
Article number	88887252
EAN-Code	4260455644198
Scope of delivery	Screw set 12 mounting screws and cage nuts 12 washers made of plastics Earthing screw Wall-mounting Assembly instructions (English, German for download)
Features	1.25-1.5mm material thickness (cold rolled steel) The door can be hinged left or right Doors is lockable Side parts removable and lockable Space for 2x 120mm fans in the lid (Item 88887269) Base and lid with cable inlets (screwed cover) Delivery is disassembled in one package