



SNB-8815

The server rack SNB-8815 impresses with its compact height of only 15U and its depth of 800mm and offers sufficient space for a variety of active and passive server & network components.

With a material thickness between 1.25 and 1.50 mm, the server rack carries a total load of up to 400kg and also complies with the IP20 protection class. The cabinet is powder-coated in RAL 9005 color and can be individually closed by the integrated tempered glass door, the back door, as well as by the split removable side panels. Cable inlets in the lid and in the floor also ensure a clean routing of the cables.

The optionally available fan element, which can be installed in the lid of the cabinet, ensures optimum ventilation and the rack also scores with two standard depth struts per side as well as optional rollers or leveling feet.

- ✓ 15U and 800mm depth
- ✓ Total load of up to 400kg
- ✓ Meets protection class IP20
- ✓ Lockable glass door, back door and side panels

Specifications

Unit	15U
Width	800mm
Depth	800mm
Max. total weight	400kg
Material front door	Tempered Glass
Material back door	Steel
Opening angle of the doors	180°
Colour	RAL 9005
IP class	Fulfills IP20
Dimensions (H/W/D)	800x800x800mm (Height with rolls +65mm; Height with feet +22-70mm)
Package dimensions (H/W/D)	1. package: 710x110x820mm 2. package: 820x820x130mm 3. package: 780x820x260mm 4. package: 825x160x120mm
Weight (net)	59.53kg
Weight (gross)	65.07kg
Packing units (VE/VPE)	Shipping unit: 1 piece (4 packages)
Warranty	24 Months
Article number	88887258
EAN-Code	4260455644259
Scope of delivery	Rolls (four pieces, two with locks) Leveling feet (four pieces) Screw set 20 mounting screws and cage nuts Two earthing cables for the doors Two cable channels over the entire height Assembly instructions (English, German for download)
Features	1.25-1.5mm material thickness (cold rolled steel) The back door can be hinged left or right Doors are lockable individually (Front door with snap lock) Doors with 1-point locking Divided sidewalls (two each side) Side parts individually lockable Preparation for the fan element Base and lid with cable inlets (screwed cover) Two depth struts per side Profile rails adjustable in depth Extensive accessories Delivery is disassembled in four packages